PHYLRICH® Defining Luxury Since 1959

Deck Tub Set with Lever Handles

208-40



TECHNICAL DETAILS

ADA Compliance: Yes Deck Thickness Maximum: 2" Deck Thickness Minimum: 1/8" Fitting Hole Diameter: 1 1/8" Number of Holes: Three Hole Number of Handles: Two Handle Spread Maximum: 12" Handle Spread Minimum: 8" Handle Turn Angle: Quarter Turn Spout Reach: 9 3/8" Spout Height: 7 5/8" Inlet Connection Type: Male 3/4" NPT Installation Type: Deck Mounted Primary Material: Brass Valve Material: Ceramic Flow Restriction: Full Flow Water Pressure Maximum: 85 PSI Water Pressure Minimum: 20 PSI Water Pressure Recommended: 60 PSI

PRODUCT FEATURES

- Style: Traditional
- Collection: Coined
- Temperature Controlled By Handles
- Lever Handles

CODES & STANDARDS



ASME A112.181/ CSA B1251, ASME 112.18.2/ CSA B125.2, ANSI NSF, CEC, Watersense 61 Sect. 9, State of MA.

WARRANTY

Mechanical Warranty: 10 Years from date of purchase. finish warranty: see catalog for further information.



