

230-40



- Style: Contemporary
- Collection: Basic II
- Temperature Controlled By Handles
- Knurled Handles
- High Arch Spout

ADA Compliance: No
 Deck Thickness Maximum: 2"
 Deck Thickness Minimum: 1/8"
 Fitting Hole Diameter: 1 1/8"
 Number of Holes: Three Hole
 Number of Handles: Two
 Handle Spread Maximum: 12"
 Handle Spread Minimum: 8"
 Handle Turn Angle: Quarter Turn
 Spout Reach: 9"
 Spout Height: 10 1/2"
 Inlet Connection Type: Male 3/4" NPT
 Installation Type: Deck Mounted
 Primary Material: Brass
 Valve Material: Ceramic
 Flow Restriction: Full Flow
 Water Pressure Maximum: 85 PSI
 Water Pressure Minimum: 20 PSI
 Water Pressure Recommended: 60 PSI

The image contains three technical drawings of a dome-shaped structure and its components. The leftmost drawing is a side elevation of the dome, showing a semi-circular arch with a height of $5\frac{1}{2}"$ [140.97] and a base width of $9"$ [230.18]. The base has a diameter of $\phi 1\frac{7}{8}"$ [47.63]. The middle drawing is a front elevation of the dome, showing a height of $10\frac{1}{2}"$ [267.97] and a base width of $4" - 6"$ [152.4]. The base has a diameter of $\phi 1\frac{3}{4}"$ [44.2]. The rightmost drawing is a side elevation of the dome, showing a height of $1\frac{5}{8}"$ [42.55] and a base width of $2\frac{1}{4}"$ [56.9]. The base has a diameter of $\phi 2\frac{1}{8}"$ [53.85].

1261 Logan Avenue, Costa Mesa, California 92626.
Phone: 714.361.4800 Fax: 714.617.3120

 **CODES & STANDARDS**
ASME A112.181/ CSA B1251, ASME 112.18.2/ CSA B125.2, ANSI NSF, CEC

Mechanical Warranty: 10 Years from date of purchase.
Finish Warranty: See catalog for further information.

Rev-