| | 5 | 4 | | 3 | | 2 | | 1 | |
|----|--|--------------------------|--|------------|------------------------------|--------------------------------|--------------------------------|--------------|------|
| E | NOTE(S): 1. PART NUMBER, "/00" DENOTES PART SHAL | | | ITEM N | O. PART NUMBER | DESCRIF | PTION | QTY. | |
| | APPLY NSF COMPLIANT GREASE TO ANY- JOINTS, AND/OR PIVOTAL POINTS. | \wedge | | 1 | 11003 | SLEEVE MOUNT, WALL MT WIDE | SPREAD | 3 | |
| | JOINTS, AND/OR PIVOTAL POINTS. 3. APPLY NSF COMPLIANT LOCTITE TO THRE/ | \wedge | | 2 | 11933/00 | TRIM PLATE, 3 HOLE, TRANSITIOI | N | 1 | E |
| | | | | 3 | 3-101/00 | ASSY, HANDLE BLADE MIX 3 | | 3 | |
| | | | | 3.1 | 10932/00 | ESCUTCHEON, HANDLE MIX SEF | RIES | 1 | |
| | 5. SILVER SOLDER JOINTS SHALL BE FULLY WI CAPILLARY ACTION AND COMPLETELY N | ON POROUS. | | 3.2 | 10923/00 | handle, blade mix series | | 1 | |
| | FOR DEEPER ESCUTCHEON: A. 3-119/00 | | | 3.3 | 92176 | WEAR WASHER | | 2 | |
| D | B. 92401 * | | | 3.4 | 92005 | SET SCREW, CUP PT 6-32 UNC T | HREAD 3/16"L | 1 | |
| | | Í | | 3.5 | 92177 | RETAINING RING, 7/16" SHAFT | | 1 | |
| | | | | 4 | 90029 | O-RING, 1-5/8"ID X 1-3/4"OD X | 1/16"THK, AS-568-029 | 3 | D |
| | | 2 | 000 | 0 | 3.1) | | | | |
| C- | | | | | | | | | C |
| В | | | | | * | | | | В |
| A | ZONE REV. | description revisions | DATE APPROVED PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF PHYLRICH. ANY | THERM. SHO | WER TRIM. THRI | | asm/prt no. 4-215/00 | | EV A |
| | FAX: 714.617.3120 Defining Luxury Since 1959 IS | | REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF PHYLRICH IS PROHIBITED. | | NER TRIM, THRI BLADE, MIX | SCALE: 1: | | | |
| | | | DO NOT SCALE DRAWING | 2 | | | 3 WEIGHT: Ibs. | SHEET 1 OF 2 | |
| | J | 4 | | 3 | | 2 | | I | |

